



General Advisory Bulletin

PGX312 Enrollment on PowerSeries Neo/Pro using external Contacts



Date: July 16, 2020

Region: Global

Product: PGX312 PowerG Wireless Outdoor Magnetic Contact

Brand: DSC

Overview

This bulletin is to inform you of the required procedure to utilize the PGX312 PowerG Wireless Outdoor Magnetic Contact's external contacts on the PowerSeries Neo and PowerSeries Pro control panels.

If the PGX312 will be using the external contact (REED SWITCH=N), then the magnet needs to be placed near to the device in order to place the reed switch in a closed/secure state. Once the magnet is in place, the option for the reed switch can be set to 'N' and the external contact option can be set to 'Y' along with the desired EOL setting.

Changes to the PowerSeries Neo and PowerSeries Pro are being investigated for future releases to eliminate the need to secure the reed switch before disabling in installers programming.

Please contact technical support for any questions related to the required enrollment procedure outlined in this bulletin.

Contact Information

Order Entry	1-888-888-7838
Sales	Contact your local sales rep. or email info@dsc.com
Technical Support	North America: +1-800-387-3630 Latin America: +1-416-645-8083 EMEA - Local: +31 475 352 722 EMEA - Toll-Free: 800-22558926 <u>APAC Local Direct Dial Numbers:</u> India: +91-80-4199-0994 China: +86-21-6163-8644 Australia: +61-28-317-1322 Oceania and New Zealand: +64-9942-4004 <u>APAC Local Toll-Free Numbers:</u> Australia: 1-800-580-946 China: 400-6711-528 or email: intrusion-support@jci.com
Product Manager	Dwayne Salsman dwayne.salsman@jci.com