

Discontinuation Notice IMPASSA Kits



Region: US

Product: IMPASSA Kits

Brand: DSC



Scope

We would like to let you know that effective immediately, the IMPASSA kits listed below will no longer be available, with no direct replacements. To assist with this transition, the replacement IMPASSA panel models listed at right can be combined with standalone detectors and communicators to make up an equivalent to each of the discontinued kits.

Affected Products

Part Number	Description	Replacement Part Number	Replacement Description
KIT457-12	IMPASSA self- contained wireless kit, containing 1 x WS4904P wireless pet-immune passive infrared detector, 1 x WS4939 four-button wireless key, 3 x WS4945 wireless door/window	SCW457J	IMPASSA standalone unit (POTS only). Includes 64 zone self-contained wireless alarm system with CP-01 software and built- in two-way voice, a 7.2V NI-MH

	contact, PTD1620U 16V 20VA transformer, telephone jack and cord. English user and installation manuals.		battery, high efficiency transformer, telephone jack and cord and English user and installation manuals.
KIT457-14	IMPASSA self- contained wireless kit, containing 1 x WS4904P wireless pet-immune passive infrared detector, 1 x WS4939 four-button wireless key, 3 x EV- DW4975 vanishing wireless door/window contacts, PTD1620U 16V 20VA transformer, telephone jack and cord. English user and installation manuals	SCW457J	IMPASSA standalone unit (POTS only). Includes 64 zone self-contained wireless alarm system with CP-01 software and built- in two-way voice, a 7.2V NI-MH battery, high efficiency transformer, telephone jack and cord and English user and installation manuals.
KIT457-95LEADT	IMPASSA panel with LTE Cellular Communicator, ADT SIM, WLS922L-433, WS4939, 3 x EV- DW4975 and a transformer.	SCW457LEADT	IMPASSA standalone unit with LTE Communicator. Includes 64 zone self-contained wireless alarm system with CP-01 software and built- in two-way voice, ADT branded lens, a 7.2V NI-MH battery, high efficiency transformer, telephone jack and cord, ADT branded user and installation manuals.
KIT457-96LEADT	IMPASSA panel with LTE Cellular Communicator, ADT SIM, WS4904P, WS4939, 3 x	SCW457LEADT	IMPASSA standalone unit with LTE Communicator. Includes 64 zone

	T	<u></u>	
	EV-DW4975 and a		self-contained
	transformer.		wireless alarm
			system with CP-01
			software and built-
			in two-way voice,
			ADT branded lens,
			a 7.2V NI-MH
			battery, high
			efficiency
			transformer,
			telephone jack and
			cord, ADT branded
			user and
			installation
			manuals.
			manuais.
			IMPASSA
			standalone unit
			with LTE
			communicator.
			Includes 64 zone
			self-contained
			wireless alarm
	IMPASSA panel with LTE Cellular Communicator, AT&T SIM, WS4904P, WS4939, 3 x EV- DW4975 and a transformer.		system with CP-01
			software and built-
		SCW457LEAT	in two-way voice,
			an integrated
KIT457-96LEAT			HSPA (3G) cellular
			communicator, a
			7.2V NI-MH
			battery, high
			efficiency
			transformer,
			telephone jack and
			cord and English
			user and
			installation
			manuals.
	Alarm.com		IMPASSA
	Interactive Kit.		standalone unit
KIT457-99AAT	Includes IMPASSA		that is 3G-Ready.
	V1.3 self-contained		Includes 64 zone
			self-contained
	wireless kit,		wireless alarm
	integrated 3G8055 AT&T cellular communicator with on-board Z-Wave	SCW457J TL8055LTVZ	
			system with CP-01
			software and built-
			in two-way voice, a
	exclusive to		7.2V NI-MH
	Alarm.com services, 1		battery, high
	x WS4904P wireless pet-immune passive		efficiency
			transformer,
	infrared detector, 1 x		telephone jack and
	WS4939 four-button		cord and English

	1	T	
wireless key, 3 x WS4945 wireless			user and installation
	door/window		manuals.
	contact, PTD1620U		manaais.
	16V 20VA		IMPASSA
	transformer and a		Alarm.com Verizon
	battery.		Dual-Path LTE/IP
			Communicator
			with back plastic
			and antennas
			and antennas
	Alarm.com		IMPASSA
	Interactive Kit.		standalone unit
	Includes IMPASSA		that is 3G-Ready.
	V1.3 self-contained		Includes 64 zone
	wireless kit,		self-contained
	integrated 3G8055I		wireless alarm
	AT&T cellular		system with CP-01
	communicator with		software and built-
	on-board Z-Wave		in two-way voice, a
	exclusive to		7.2V NI-MH
	Alarm.com services,		battery, high
KIT457-99AIAT	integrated image	00\\\457.1	efficiency
	sensor module, 1 x	SCW457J	transformer,
	IS214 Image Sensor,	TL8055LTVZ	telephone jack and
	1 x WS4904P wireless		cord and English
	pet-immune passive		user and
	infrared detector, 1 x		installation
	WS4939 four-button		manuals.
	wireless key, 3 x		INADACCA
	WS4945 wireless door/window		IMPASSA
	contact, PTD1620U		Alarm.com Verizon
	16V 20VA		Dual-Path LTE/IP Communicator
	transformer and a battery.		with back plastic
			and antennas
			and antennas
			IMPASSA
			standalone unit
			with LTE
			Communicator.
			Includes 64 zone
	IMPASSA panel with		self-contained
KIT457-99LEADT	LTE Cellular Communicator, ADT SIM, WS4904P, WS4939, 3 x WS4945 and a transformer.		wireless alarm
			system with CP-01
		SCW457LEADT	software and built-
			in two-way voice,
			ADT branded lens,
			a 7.2V NI-MH
			battery, high
			efficiency
			transformer,
			telephone jack and
			cord, ADT branded

			user and installation manuals.
SCW457AATNT	Alarm.com IMPASSA V1.3 standalone unit. Includes 64 zone self-contained wireless alarm system with CP-01 software and built-in two-way voice, an integrated 3G8055 AT&T cellular communicator with on-board Z-Wave exclusive to Alarm.com, a 7.2V NI-MH battery, telephone jack and cord and English user and installation manuals. Transformer is not included.	NA	

Please be advised that effective immediately, the IMPASSA products listed above will be discontinued. New orders for these products will be accepted only while quantities last.

Schedule		
End-of-Life Announcement	June, 2020	
Last Buy Date	Effective Immediately	
Last Ship Date	N/A	

Note: Due to material availability, orders significantly higher than forecast or historical run rate may not be accepted.

Contact Information	
Order Entry	1-888-888-7838
Sales	Contact your local sales rep. or email info@dsc.com
Technical Support	North America: +1-800-387-3630 or email: intrusion-support@jci.com
Product Manager	Curtis Jay curtis.jay@jci.com





Johnson Controls

5757 N. Green Bay Avenue | P.O. Box 591 Milwaukee, WI 53201 | 441-524-1200