

## PG9936H Heat Detector

Reliable, Early Fire Detection



# Heat Only Detector For areas such as kitchens and garages where

the installation of a smoke detector is not recommended.



# Temperature Warning Temperatures exceeding 57°C (135°F) trigger

the built-in 85 dB alarm, flash the LED light, and activate IO Panel notifications and siren.



#### PowerG

Wireless security eliminates the need for wires, providing secure and reliable communication with an industry-leading range and encryption.



### 3-Year Battery Life

Adaptive transmission power maximizes battery life. (Typical Use)



Easy Installation
Quick wireless installation allows for flexible placement and easy maintenance.



# Compatible Panels Works with: IQ Panel 2+, IQ Panel 4,

IQ4 Hub, IQ4 NS, PowerSeries Neo, PowerSeries Pro.







## **Specifications**

Items	PG9936H
Dimensions	125 x 63mm (5 x 2.5in)
Battery Life	3 years (typical use)
Battery Type	3 AAA batteries (included)
Weight	243g (8.75oz)
Siren	Built-in 85db
Alarm TriggerTemperature	Exceed 57°C (135°F)
Sensing Technology	Thermistor-based sensing
Installation Locations	Wall or Ceiling installation, with bracket
Operating Temperature	4.4°C to 37.8°C (40°F to 100°F)
Operating Environment	Indoors
Approvals	FCC, UL, CSFM (for PGx936)

For further information please refer to www.dsc.com





