



UOXX.S4019 Control Unit Accessories, System

[Page Bottom](#)

Control Unit Accessories, System

[See General Information for Control Unit Accessories, System](#)

DIGITAL SECURITY CONTROLS, DIV OF TYCO SAFETY PRODUCTS CANADA LTD

S4019

95 BRIDGELAND AVE
TORONTO, ON M6A 1Y7 CANADA

End of line resistors, Model(s) EOLR-1, EOLR-2, EOLR-3

Fire alarm communicator for central station service fire alarm - commercial: Ethernet/Internet communicator (Other Transmission Technologies) signaling devices, Model(s) T-Link TL250, T-Link TL300, T-Link TL300 CF, suitable for use as a single communications technology (no need for two phone lines) when supervision heartbeat is enabled and window of supervision at supervising station is set for 5 minutes. Also suitable for use as a multiple communications technologies when used in conjunction with another type of communicator (for example a back-up dialer (DACT) over the telephone line). In this configuration the two communication methods used shall supervise each other and failure of each channel shall be annunciated at the supervising station within 24h (c).

Fire alarm communicator for central station service fire alarm - commercial: RF communicator (GSM-GPRS network/Other Transmission Technologies) signaling devices, Model(s) GS3055-I CF, 3G3070-CF suitable for use as a single communications technology (no need for two phone lines) when supervision heartbeat is enabled and window of supervision at supervising station is set for 5 minutes. Also suitable for use as a multiple communications technologies when used in conjunction with another type of communicator (for example back-up to a dialer (DACT) over the phone line). In this configuration the two communication methods used shall supervise each other and failure of each channel shall be annunciated at the supervising station within 24h (c).

(c) - For use with separately Listed compatible control units with integral or Listed remote DACT or as a standalone/sole communicator (no need for two phone lines) as indicated in the installation instructions.

[Last Updated](#) on 2011-12-23

[Questions?](#)

[Print this page](#)

[Terms of Use](#)

[Page Top](#)

© 2012 UL LLC

When the UL Leaf Mark is on the product, or when the word "Environment" is included in the UL Mark, please search the [UL Environment database](#) for additional information regarding this product's certification.

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Listed and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Designs and/or Listings (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from UL" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "© 2012 UL LLC".