



ANSR.BP6082 Intrusion-detection Units

[Page Bottom](#)

Intrusion-detection Units

[See General Information for Intrusion-detection Units](#)

DIGITAL SECURITY CONTROLS, DIV OF TYCO SAFETY PRODUCTS CANADA LTD

BP6082

95 BRIDGELAND AVE
TORONTO, ON M6A 1Y7 CANADA

Model DI-50 followed by ALU, AU, AWU, BLU, BWU, CLU, CU or CWU passive infrared detectors for use with the following lenses: DI-50L1, -50L2, -50L3.

Models BV-100, BV-101, BV-102, BV-200, BV-201, BV-202, BV-300, BV-301, BV-302, BV-300D, BV-301D, BV-302D, BV-500, BV-501, BV-502, PBV-300D, PBV-301D, PBV-302D, PBV-200, PBV-201, PBV-202, PBV-300, PBV-301, PBV-302, PBV-500, PBV-501, PBV-502 infrared detectors with the following lenses: BV-L1, -L2, -L3, -L4.

Models BV-300P, BV-301P, BV-302P, BV-300DP, BV-301DP, BV-302DP, PBV-300P, PBV-301P, PBV-302P, PBV-300DP, PBV-301DP, PBV-302DP infrared detectors.

Models BV-400UL, -401UL, -402UL infrared detectors with the following lenses: BV-L1, -L2, -L3, -L4.

Models BV-600, BV-601, BV-602, PBV-600, PBV-601, PBV-602 PIRs with standard lens only.

Models BV-500GB, BV-501GB, BV-502GB, PBV-500GB, PBV-501GB, PBV-502GB combination passive infrared/glassbreak detectors, with standard lens only, ceiling mount.

Model PAMB/AMB-500 passive infrared detector, with standard lens only. Used with control units as indicated in the installation instructions.

Models F2-200, -201, -202, -210, -211, -212, -220, -221, -222, PF2-200, -201, -202, -220, -221, -222, -210, -211, -212 combination infrared/microwave detectors.

Models LC-100-PI, LC-120-PI, LC-101-CAM, LC-121-CAM (Models LC-101-CAM and LC-121-CAM, Camera and audio features are for supplementary use only).

Models LC-103-PIMSK, LC-123-PIMSK, LC-104-PIMW, LC-124-PIMW Combination PIR/Microwave.

Models AC-100, AC-101, AC-102, PAC-100, PAC-101, PAC-102 audio glass break detectors; Models AC-500, AC-501, AC-502 glass break detectors. Used with Listed compatible control unit as indicated in the installation instructions.

Models PWLS-914, WLS-914, PWLS914-433, WLS914-433 dual passive infrared detectors for use with a compatible receiver/control unit as indicated in the installation instructions.

Models WLS912, PWLS912, WLS912L-433, wireless glassbreak detectors for use with a compatible receiver/control unit as indicated in the installation instructions.

Models EC-300, EC-301, EC-302 PIRs for use with the following lenses: BV-L1, -L1-UV, -L2-UV, -L3, -L3-UV, -L4, -L4-UV.

Models EC-300D, EC-301D, EC-302D, PEC-300D, PEC-301D, PEC-302D to be use with standard lens BV-L1-UV and optional BV-LZ-UV, BV-L3-UV, BV-L4-UV.

Models EC-3000DP, EC-301DP, EC-302DP, PEC-300DP, PEC-301DP, PEC-302DP to be used with fresnel lens only.

Models PAMA/AMA100, PAMB/AMB300, PAMB/AMB600, PWLS/WLS 904, PWLS/WLS-904P, PWLS/WLS 904-433, PWLS/WLS-904P-433, WS4904, WS4904P. Used with Listed compatible control units as indicated in the installation instructions.

Models ST300D, ST301D, ST302D.

Wireless intrusion detection units, Models PG9904, PG9904P, PG9934, PG9934P, PG9974, PG9974P, PG9924 passive infrared detector for use

with the PowerMaster-10 PG2 and PowerMaster-30 PG2.

Last Updated on 2013-08-22

[Questions?](#)

[Print this page](#)

[Terms of Use](#)

[Page Top](#)

© 2013 UL LLC

When the UL Leaf Mark is on the product, or when the word "Environment" is included in the UL Mark, please search the [UL Environment database](#) for additional information regarding this product's certification.

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from UL" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "© 2013 UL LLC".