

AMCXC.S4019 - CENTRAL AND MONITORING STATION BURGLAR ALARM SYSTEM UNITS

Central and Monitoring Station Burglar Alarm System Units

See General Information for Central and Monitoring Station Burglar Alarm System Units

DIGITAL SECURITY CONTROLS, DIV OF TYCO SAFETY PRODUCTS CANADA LTD
95 BRIDGELAND AVE
TORONTO, ON M6A 1Y7 CANADA

S4019

Investigated to CAN/ULC-S304 (2nd Ed.)

Accessory, dual dialer communication interfaces, Model(s) *PC4701*

Accessory, ethernet communicators, Model(s) *T-Link TL250, T-Link TL300*

Accessory, keypads, Model(s) *LCD4501Z(T)*

Accessory, PGM output modules, Model(s) *PC4216*

Accessory, power supply modules, Model(s) *PC4204CX, PC4204CXCF*

Accessory, serial output modules, Model(s) *PC4401, KT4401VK*

Accessory, zone expanders modules, Model(s) *PC4108A, PC4116*

Auxiliary power supplies, Model(s) *PC5200, PC5204*

Central station alarm units (Class II, input: 16.5Vac, 60Hz, 40VA), "DSC Series", Model(s) *PC1864, PC1832, PC1616*

Control unit accessory, 3G cellular alarm communicating interfaces, Model(s) *3G4000 or 3G4000RF GSM-GPRS/3G, an Active (A1-A4) communication system when both heartbeat and encryption are enabled, or a passive communication system with level P2 line security.*

3G8080 or 3G8080I 3G, an Active (A1-A4) communication system when both heartbeat and encryption are enabled, or a passive communication system with level P3 line security.

Control unit accessory, alarm communicators, Model(s) *3G4010 GSM-GPRS/3G, for use in an active communication system (A1-A4), or in a passive communication system (P1 or P2 when used in conjunction with DACT).*

3G4010CF GSM-GPRS/3G, for use in an active communication system (A1-A4), or in a passive communication system (P1 or P2 when used in conjunction with DACT).

Control unit accessory, CDMA cellular alarm communicating interfaces, Model(s) *CD8080 or CD8080I CDMA, an Active (A1-A4) communication system when both heartbeat and encryption are enabled, or a passive communication system with level P3 line security.*

Control unit accessory, interfaces, Model(s) *3G3070 GSM-GPRS/3G, a passive communication system with level P2 line security. Internal 12V, minimum 1.2 AH rechargeable battery is required for Low Power Mode (JP3 OFF).*

3G3070-RF GSM-GPRS/3G, a passive communication system with level P2 line security, Internal 12V, minimum 7 AH rechargeable battery.

GS3055-I GSM-GPRS

GS3055-I, GS3060 or GSM-GPRS, classified as a passive communication system with level P2 line security. Internal 12V, minimum 1.2 AH rechargeable battery is required for Low Power Mode (JP3 OFF);.

Control unit accessory, keypads, compatible with alarm controllers HS2128, HS2064, HS2032 or, HS2016, Model(s) HS2LCD, HS2LCDP, HS21CN, HS21CNP, HS2LED, HS2TCHP

Control unit accessory, large audio stations, Model(s) PC5964E

Control unit accessory, small audio stations, Model(s) PC5961E

Control unit accessory, telco voltage boosters, Model(s) GS-BOOST, used only with GS3060 when interfacing with alarm control panels that require a higher simulated Telco line voltage.

Control unit subassemblies, Model(s) 3G3070 PCB, a passive communication system with level P2 line security. Internal 12V, minimum 1.2 AH rechargeable battery is required for Low Power Mode (JP3 OFF)..

3G4010 PCB

Control unit subassembly, alarm controllers, Model(s) HS2128, HS2064, HS2032, HS2016

Control unit subassembly, audio verification interfaces, Model(s) HSM2955, HSM2955R

Control unit subassembly, CDMA cellular alarm communicators, Model(s) CD8055 NEO, CD8055I NEO CDMA Interface

Control unit subassembly, PGM output modules, Model(s) HSM2208

Control unit subassembly, power supplies, Model(s) HSM2300, HSM2204

Control unit subassembly, zone expanders, Model(s) HSM2108

Fire alarm and security subassembly, Model(s) IP/GSM-GPRS Dual Alarm Communication Interfaces-TL260GS, TL260GS-SM, TL260GS-RS, TL2603GR, TL2803GR, TL2803GRE, TL2603G, TL2803G, TL2803GE; GSM-GPRS Alarm Communication Interfaces-GS2060, GS2060-SM, GS2060-RS, 3G2060R, 3G2060, 3G2080, 3G2083E, 3G2080R, 3G2803RE; IP Alarm Communication Interface-TL260, TL280, TL280E, TL260R, TL280R, TL280RE, TL260-SM, TL260-RS; classified as transmitting modules in an Active (A1-A4) communication system, or in a Passive (P1-P3) communication system (may be used in conjunction with a Listed DACT), for use only with DSC's separately Listed control units PC1864, PC1832, PC1616, HS2128, HS2064, HS2032 or HS2016 and central station receivers.

TL280LER, TL280LE IP/LTE Dual Alarm Communication Interface, Model LE2080R, LE2080 LTE Alarm Communication Interface; classified as transmitting modules in an Active (A1-A4) communication system, or in a Passive (P1-P3) communication system (may be used in conjunction with a Listed DACT), for use only with DSC's separately Listed control units HS2128, HS2064, HS2032 or HS2016 and central station receivers

Fire alarm and security subassembly, communication expansion interface boards, Model(s) PCL-422

Output modules, Model(s) PC5208

Subscriber's control units, Model(s) PC4020

Subscribers' unit accessory, keypads, Model(s) LCD5511, LED5511, PK5500, PK5501, PK5508, PK5516, PTK5507

Zone expanders, Model(s) PC5108

Investigated to CAN/ULC-S304:2016 (3rd Ed.)

Subassembly, Communicator PCB assemblies, Model(s) LE4010 PCB, LE4020 PCB

Investigated to CAN/ULC-S304:2016 (3rd Ed.)

Communication Channel Security Level & Specifications

Model	Product	Notes Active	Passive	Conditions and Notes
Investigated to CAN/ULC-S304:2016 (3rd Ed.)				

TL880LE	IP/LTE Alarm Communicator	-	A4	P3	For use in an active communication system (A1-A4), or in a passive communication system (P1, P2) when used in conjunction with DACT
LE4000	LTE Alarm Communication Interface	-	A4	P2	For use only with DSC's separately Listed control units HS2128, HS2064, HS2032 or HS2016 and central station receivers
LE4010, LE4010CF	LTE Alarm Communication Interface	-	A4	P2	For use in an active communication system (A1-A4), or in a passive communication system (P1, P2) when used in conjunction with DACT)
LE4020, LE4020CF	LTE Alarm Communication Interface	-	A4	P2	For use in an active communication system (A1-A4), or in a passive communication system (P1, P2) when used in conjunction with DACT)

Model	Equipment Type	Security Level	Notes
Investigated to CAN/ULC-S304:2016 (3rd Ed.)			
HS3128, HS3032	Alarm controllers	IV	Wireless devices only to be used in Security Level I applications
ADC-620TE	Communicator Board Subassembly	IV	-
3G9080	Control unit subassemblies, 3G Alarm Communication Interfaces	IV	For use with combination control unit subassembly HS3128 PCB, HS3032 PCB
3H9080	Control unit subassemblies, 3G Alarm Communication Interfaces	IV	For use with combination control unit subassembly HS3128 PCB, HS3032 PCB
HS3128 PCB, HS3032 PCB	Control unit subassemblies, alarm controllers	IV	Wireless devices only to be used in Security Level I applications
HS3204CX	Control unit subassemblies, Corbus repeaters, power supply modules	IV	-

HS3010C	Control unit subassemblies, enclosures	IV	For use with combination control unit subassembly HS3128 PCB, HS3032 PCB
HS3010CR	Control unit subassemblies, enclosures	IV	For use with combination control unit subassembly HS3128 PCB, HS3032 PCB
HS3020C	Control unit subassemblies, enclosures	IV	For use with combination control unit subassembly HS3128 PCB, HS3032 PCB
LE9080	Control unit subassemblies, LTE/3G Alarm Communication Interfaces	IV	For use with combination control unit subassembly HS3128 PCB, HS3032 PCB
HS3350	Control unit subassemblies, power supply modules	IV	-
HSM3408	Control unit subassemblies, zone expanders	IV	For use with combination control unit subassembly HS3128 PCB, HS3032 PCB
TL880LE	IP/LTE Alarm Communicator	IV	-
PG9949, PG9929, PG9939	Keyfob	I	For use with alarm controller HS2128, HS2064, HS2032 or HS2016, used in conjunction with the compatible wireless transceiver HSM2HOST9 or keypads with integrated wireless transceiver HS2LCDRF(P)9 or HS2ICNRF(P)9
HS2LCDRF9, HS2LCDRFP9, HS2ICNRF9, HS2ICNRF9P9	Keypad with RF Transceiver	I	For use with alarm controller HS2128, HS2064, HS2032 or HS2016
LE4000	LTE Alarm Communication Interface	IV	-
LE4010, LE4010CF	LTE Alarm Communication Interface	IV	-
LE4020, LE4020CF	LTE Alarm Communication Interface	IV	-

PG9920	RF Repeaters	I	For use with alarm controller HS2128, HS2064, HS2032 or HS2016
HSM2HOST9	RF Transceivers	I	For use with alarm controller HS2128, HS2064, HS2032 or HS2016
HS2LCDWFPV9, HS2LCDWFP9, HS2LCDWF9	Wireless Keypads	I	For use with combination control unit HS2128, HS2064, HS2032 or HS2016, used in conjunction with the compatible wireless transceiver HSM2HOST9 or keypads with integrated wireless transceiver HS2LCDRF(P)9 or HS2ICNRF (P)9

Last Updated on 2018-12-12

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from UL" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "© 2019 UL LLC"