

**TCB****GRANT OF EQUIPMENT  
AUTHORIZATION****TCB****Certification****Issued Under the Authority of the  
Federal Communications Commission****By:****DEKRA Testing and Certification, S.A.U.  
Parque Tecnologico de Andalucia, Calle Severo  
Ochoa 2 y 6  
Campanillas - Malaga, 29590  
Spain****Date of Grant: 12/15/2017****Application Dated: 12/15/2017****Digital Security Controls Ltd.  
3301 Langstaff Road  
Concord, Ontario, L4K 4L2  
Canada****Attention: Dan Nita , Approvals Manager****NOT TRANSFERABLE**

EQUIPMENT AUTHORIZATION is hereby issued to the named GRANTEE, and is VALID ONLY for the equipment identified hereon for use under the Commission's Rules and Regulations listed below.

**FCC IDENTIFIER:** F5317LE4000**Name of Grantee:** Digital Security Controls Ltd.**Equipment Class:** PCS Licensed Transmitter**Notes:** LTE Cellular Alarm Communicator

<u>Grant Notes</u>	<u>FCC Rule Parts</u>	<u>Frequency Range (MHZ)</u>	<u>Output Watts</u>	<u>Frequency Tolerance</u>	<u>Emission Designator</u>
	22H	826.4 - 846.6	0.2366	1.0 PM	4M09G9W
	22H	826.4 - 846.6	0.236	1.0 PM	4M09G9W
	22H	826.4 - 846.6	0.1641	1.0 PM	4M09G9W
	24E	1852.4 - 1907.6	0.2239	1.0 PM	4M08G9W
	24E	1852.4 - 1907.6	0.2234	1.0 PM	4M08G9W
	24E	1852.4 - 1907.6	0.1667	1.0 PM	4M08G9W
	24E	1850.7 - 1909.3	0.2004	1.0 PM	1M10G7D
	24E	1850.7 - 1909.3	0.1722	1.0 PM	1M10W7D
	24E	1851.5 - 1908.5	0.2	1.0 PM	2M74G7D
	24E	1851.5 - 1908.0	0.1694	1.0 PM	2M72W7D
	24E	1852.5 - 1907.5	0.2004	1.0 PM	4M51G7D
	24E	1852.5 - 1907.5	0.1738	1.0 PM	4M48W7D
	24E	1855.0 - 1905.0	0.2123	1.0 PM	9M08G7D
	24E	1855.0 - 1905.0	1.1828	1.0 PM	9M07W7D
	24E	1857.5 - 1902.5	0.227	1.0 PM	13M5G7D
	24E	1857.5 - 1902.5	0.1977	1.0 PM	13M5W7D
	24E	1860.0 - 1900.0	0.2163	1.0 PM	18M6G7D
	24E	1860.0 - 1900.0	0.1888	1.0 PM	18M5W7D
	27	1710.7 - 1754.3	0.1919	1.0 PM	1M10G7D
	27	1710.7 - 1754.3	0.1644	1.0 PM	1M10W7D
	27	1711.5 - 1753.5	0.1897	1.0 PM	2M74G7D
	27	1711.5 - 1753.5	0.1663	1.0 PM	2M73W7D
	27	1712.5 - 1752.5	0.1919	1.0 PM	4M50G7D
	27	1712.5 - 1752.5	0.1679	1.0 PM	4M48W7D
	27	1715.0 - 1750.0	0.173	1.0 PM	9M05G7D
	27	1715.0 - 1750.0	0.173	1.0 PM	9M06W7D

<b>27</b>	<b>1717.5 - 1747.5</b>	<b>0.2123</b>	<b>1.0 PM</b>	<b>13M4G7D</b>
<b>27</b>	<b>1717.5 - 1747.5</b>	<b>0.1866</b>	<b>1.0 PM</b>	<b>13M5W7D</b>
<b>27</b>	<b>1720.0 - 1745.0</b>	<b>0.2148</b>	<b>1.0 PM</b>	<b>18M5G7D</b>
<b>27</b>	<b>824.7 - 848.3</b>	<b>0.2004</b>	<b>1.0 PM</b>	<b>18M5W7D</b>
<b>22H</b>	<b>824.7 - 848.3</b>	<b>0.2004</b>	<b>1.0 PM</b>	<b>1M10G7D</b>
<b>22H</b>	<b>825.7 - 848.3</b>	<b>0.1722</b>	<b>1.0 PM</b>	<b>1M10W7D</b>
<b>22H</b>	<b>825.5 - 847.5</b>	<b>0.2183</b>	<b>1.0 PM</b>	<b>2M74G7D</b>
<b>22H</b>	<b>825.5 - 847.5</b>	<b>0.1871</b>	<b>1.0 PM</b>	<b>2M72W7D</b>
<b>22H</b>	<b>826.5 - 846.5</b>	<b>0.2163</b>	<b>1.0 PM</b>	<b>4M51G7D</b>
<b>22H</b>	<b>826.5 - 846.5</b>	<b>0.1879</b>	<b>1.0 PM</b>	<b>4M49W7D</b>
<b>22H</b>	<b>829.0 - 844.0</b>	<b>0.1875</b>	<b>1.0 PM</b>	<b>9M09G7D</b>
<b>22H</b>	<b>829.0 - 844.0</b>	<b>0.1875</b>	<b>1.0 PM</b>	<b>9M09W7D</b>
<b>27</b>	<b>699.7 - 715.3</b>	<b>0.2094</b>	<b>1.0 PM</b>	<b>1M10G7D</b>
<b>27</b>	<b>699.7 - 715.3</b>	<b>0.1828</b>	<b>1.0 PM</b>	<b>1M10W7D</b>
<b>27</b>	<b>700.5 - 714.5</b>	<b>0.2084</b>	<b>1.0 PM</b>	<b>2M73G7D</b>
<b>27</b>	<b>701.5 - 713.5</b>	<b>0.2051</b>	<b>1.0 PM</b>	<b>2M72W7D</b>
<b>27</b>	<b>701.5 - 713.5</b>	<b>0.2051</b>	<b>1.0 PM</b>	<b>4M49G7D</b>
<b>27</b>	<b>701.5 - 713.5</b>	<b>0.1807</b>	<b>1.0 PM</b>	<b>4M48W7D</b>
<b>27</b>	<b>704.0 - 711.0</b>	<b>0.2028</b>	<b>1.0 PM</b>	<b>9M02G7D</b>
<b>27</b>	<b>704.0 - 711.0</b>	<b>0.177</b>	<b>1.0 PM</b>	<b>9M02W7D</b>
<b>27</b>	<b>779.5 - 784.5</b>	<b>0.2061</b>	<b>1.0 PM</b>	<b>4M52G7D</b>
<b>27</b>	<b>779.5 - 784.5</b>	<b>0.1778</b>	<b>1.0 PM</b>	<b>4M49W7D</b>
<b>27</b>	<b>782.0 - 782.0</b>	<b>0.1963</b>	<b>1.0 PM</b>	<b>9M09G7D</b>
<b>27</b>	<b>782.0 - 782.0</b>	<b>0.171</b>	<b>1.0 PM</b>	<b>9M11W7D</b>

Output power is conducted.

This device is approved for mobile and fixed use with respect to RF exposure compliance. The antenna of this transmitter must provide a separation distance of at least 20 cm from all persons. Installers and end-users must be provided with operating conditions for satisfying RF exposure compliance.

Multi-transmitter, supporting simultaneous transmission configurations, have not been evaluated and shall be evaluated according to KDB Publication 447498 and §2.947(f) composite system and §2.1 end product terms and concepts.