

TCB**GRANT OF EQUIPMENT
AUTHORIZATION****TCB**

Certification
Issued Under the Authority of the
Federal Communications Commission
By:

Siemic Inc.
 775 Montague Expressway
 Milpitas, CA 95035

Date of Grant: 03/28/2018

Application Dated: 03/28/2018

Digital Security Controls Ltd.
 3301 Langstaff Road
 Concord, Ontario, L4K 4L2
 Canada

Attention: Dan Nita , Approvals Manager

NOT TRANSFERABLE

EQUIPMENT AUTHORIZATION is hereby issued to the named GRANTEE, and is
 VALID ONLY for the equipment identified hereon for use under the Commission's Rules
 and Regulations listed below.

FCC IDENTIFIER: F5318LE2077
Name of Grantee: Digital Security Controls Ltd.
Equipment Class: PCS Licensed Transmitter
Notes: LTE Cellular Alarm Communicator
Modular Type: Limited Single Modular

<u>Grant Notes</u>	<u>FCC Rule Parts</u>	<u>Frequency Range (MHZ)</u>	<u>Output Watts</u>	<u>Frequency Tolerance</u>	<u>Emission Designator</u>
	22H	826.4 - 846.6	0.226	1.0 PM	4M08F9W
	22H	826.4 - 846.6	0.178	1.0 PM	4M08F9W
	22H	826.4 - 846.6	0.152	1.0 PM	4M08F9W
	24E	1852.4 - 1907.6	0.359	1.0 PM	4M08F9W
	24E	1852.4 - 1907.6	0.282	1.0 PM	4M08F9W
	24E	1852.4 - 1907.6	0.245	1.0 PM	4M08F9W
	24E	1850.7 - 1909.3	0.338	1.0 PM	1M09G7D
	24E	1850.7 - 1909.3	0.287	1.0 PM	1M08W7D
	24E	1851.5 - 1908.5	0.338	1.0 PM	2M69G7D
	24E	1851.5 - 1908.5	0.279	1.0 PM	2M69W7D
	24E	1852.5 - 1907.5	0.339	1.0 PM	4M47G7D
	24E	1852.5 - 1907.5	0.287	1.0 PM	4M47W7D
	24E	1855.0 - 1905.0	0.331	1.0 PM	8M97G7D
	24E	1855.0 - 1905.0	0.277	1.0 PM	8M96W7D
	24E	1857.5 - 1902.5	0.341	1.0 PM	13M5G7D
	24E	1857.5 - 1902.5	0.282	1.0 PM	13M4W7D
	24E	1860.0 - 1900.0	0.339	1.0 PM	17M9G7D
	24E	1860.0 - 1900.0	0.293	1.0 PM	17M9W7D
	27	1710.7 - 1754.3	0.296	1.0 PM	1M08G7D
	27	1710.7 - 1754.3	0.253	1.0 PM	1M08W7D
	27	1711.5 - 1753.5	0.288	1.0 PM	2M69G7D
	27	1711.5 - 1753.5	0.252	1.0 PM	2M69W7D
	27	1712.5 - 1752.5	0.289	1.0 PM	4M47G7D
	27	1712.5 - 1752.5	0.246	1.0 PM	4M47W7D
	27	1715.0 - 1750.0	0.293	1.0 PM	8M97G7D

27	1715.0 - 1750.0	0.244	1.0 PM	8M97W7D
27	1717.5 - 1747.5	0.296	1.0 PM	13M5G7D
27	1717.5 - 1747.5	0.25	1.0 PM	13M4W7D
27	1720.0 - 1745.0	0.293	1.0 PM	18M0G7D
27	1720.0 - 1745.0	0.25	1.0 PM	18M0W7D
27	699.7 - 715.3	0.077	1.0 PM	1M09G7D
27	699.7 - 715.3	0.063	1.0 PM	1M08W7D
27	700.5 - 714.5	0.078	1.0 PM	2M69G7D
27	700.5 - 714.5	0.063	1.0 PM	2M69W7D
27	701.5 - 713.5	0.076	1.0 PM	4M46G7D
27	701.5 - 713.5	0.063	1.0 PM	4M47W7D
27	704.0 - 711.0	0.077	1.0 PM	8M98G7D
27	704.0 - 711.0	0.063	1.0 PM	8M98W7D
27	779.5 - 784.5	0.118	1.0 PM	4M47G7D
27	779.5 - 784.5	0.096	1.0 PM	4M47W7D
27	782.0 - 782.0	0.115	1.0 PM	8M96G7D
27	782.0 - 782.0	0.095	1.0 PM	8M95W7D
22H	824.7 - 848.3	0.189	1.0 PM	1M09G7D
22H	824.7 - 848.3	0.154	1.0 PM	1M08W7D
22H	825.5 - 847.5	0.193	1.0 PM	2M69G7D
22H	825.5 - 847.5	0.155	1.0 PM	2M69W7D
22H	826.5 - 846.5	0.187	1.0 PM	4M47G7D
22H	826.5 - 846.5	0.155	1.0 PM	4M47W7D
22H	829.0 - 844.0	0.188	1.0 PM	8M97G7D
22H	829.0 - 844.0	0.154	1.0 PM	8M97W7D
27	706.5 - 713.5	0.079	1.0 PM	4M48G7D
27	706.5 - 713.5	0.065	1.0 PM	4M48W7D
27	709.0 - 711.0	0.079	1.0 PM	8M96G7D
27	709.0 - 711.0	0.066	1.0 PM	8M95W7D

Limited Modular Approval. Power Output listed is ERP for Part 22, and EIRP for Part 24; Part 27 below 1GHz is ERP, and above 1GHz is EIRP. The antenna(s) used for this transmitter must be installed to provide a separation distance of at least 20 cm from all persons and must not be co-located or operating in conjunction with any other antenna or transmitter, except in accordance with FCC multi-transmitter product procedures. End-users must be provided with transmitter operating conditions for satisfying RF exposure compliance.