UL Online Certifications Directory

OCD Home Quick Guide Contact Us UL.com

ANSR.BP6082 Intrusion-detection Units

Page Bottom

Intrusion-detection Units

See General Information for Intrusion-detection Units

DIGITAL SECURITY CONTROLS, DIV OF TYCO SAFETY PRODUCTS CANADA LTD 3301 LANGSTAFF RD

BP6082

3301 LANGSTAFF RD CONCORD, ON L4K 4L2 CANADA

Model DI-50 followed by ALU, AU, AWU, BLU, BWU, CLU, CU or CWU passive infrared detectors for use with the following lenses: DI-50L1, -50L2, -50L3.

Models BV-100, -101, -102, -200, -201, -202, -300, -300D, -301, -301D, -302, -302D, -500, -501, -502, P-BV-300D, P-BV-301D, P-BV-302D, PBV-200, -201, -202, -300, -301, -302, -500, -501, -502 infrared detectors with the following lenses: BV-L1, -L2, -L3, -L4.

Models BV-300P, BV-301P, BV-302P, BV-300DP, BV-301DP, BV-302DP, PBV-300P, PBV-301P, PBV-302P, PBV-300DP, PBV-301DP, PBV-302DP infrared detectors.

Models BV-400UL, -401UL, -402UL infrared detectors with the following lenses: BV-L1, -L2, -L3, -L4.

Models BV-600, -601, -602, PBV-600, -601, -602 PIRs with standard lens only.

Models PBV/BV-500GB, -501GB, -502GB combination passive infrared/glassbreak detectors, with standard lens only.

Model PAMB/AMB-500 passive infrared detector, with standard lens only. Used with control units as indicated in the installation instructions.

Models F2-200, -201, -202, -210, -211, -212, -220, -221, -222, PF2-200, -201, -202, -220, -221, -222, -210, -211, -212 combination infrared/microwave detectors.

Models LC-100-PI, LC-120-PI, LC-101-CAM, LC-121-CAM (Models LC-101-CAM and LC-121-CAM, Camera and audio features are for supplementary use only).

Models LC-103-PIMSK, LC-123-PIMSK, LC-104-PIMW, LC-124-PIMW Combination PIR/Microwave.

Models PAC/AC-100, -101, -102 audio glass break detectors; Models AC-500, AC-501, AC-502 glass break detectors. Used with Listed compatible control unit as indicated in the installation instructions.

Models PWLS-914, WLS-914, PWLS914-433, WLS914-433 dual passive infrared detectors for use with a compatible receiver/control unit as indicated in the installation instructions.

Models PWLS912-433, PWLS912L-433, WLS912/PWLS912, WLS912-433, WLS912L-433, wireless glassbreak detectors for use with a compatible receiver/control unit as indicated in the installation instructions.

Models EC-300, -301, -302 PIRs for use with the following lenses: BV-L1, -L1-UV, -L2-UV, -L3, -L3-UV, -L4, -L4-UV.

Models P/EC-300D, -301D, -302D to be use with standard lens BV-L1-UV and optional BV-LZ-UV, BV-L3-UV, BV-L4-UV.

Models P/EC-3000DP, -301DP, -302DP to be used with fresnel lens only.

Models PAMA/AMA100, PAMB/AMB300, PAMB/AMB600, PWLS/WLS 904, PWLS/WLS-904P, PWLS/WLS 904-433, PWLS/WLS-904P-433, PWLS/WLS-904PL-433, (fresnel lens), WLS904L-433NA(1), WLS904PL-433NA(1), WS4904 and WS4904P. Used with Listed compatible control units as indicated in the installation instructions.

Models ST300D, ST301D, ST302D.

Last Updated on 2007-05-21

Questions?

®

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Listed and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Designs and/or Listings (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from Underwriters Laboratories Inc." must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "Copyright © 2008 Underwriters Laboratories Inc.®"

An independent organization working for a safer world with integrity, precision and knowledge.

