Save Time with Multiple Mounting Options & Pre-Installed Batteries

Practically unnoticeable once installed, the compactly designed EV-DW4955 wireless mini door/window contact is ideal for tough-to-fit installations and features a generous magnet gap of 5/8" (16 mm) that easily accommodates larger door or window frames. The contact also features a pre-installed coin cell battery. By having batteries pre-installed, installers save time as they don't have to handle batteries or open casings to insert them prior to mounting. Multiple mounting options further help to reduce installation time. The EV-DW4955 is built with reliable 433 MHz technology and is compatible with all current DSC wireless receivers.





Product Features:

- ► Small, compact design
- ► Long-life lithium coin cell battery included
- ► 5/8" (16 mm) maximum magnet gap
- Multiple mounting options (screws and double-sided tape included)
- Smooth-back plastics
- ► Case/Wall tamper
- Reliable 433 MHz technology
- ► FCC/IC listed

Quicker Installations

The EV-DW4955 features a pre-installed battery that is activated by installers through a pull tab. This helps reduce installation time as casings don't need to be opened for battery insertion. Simply draw the activation pull tab and mount the contact. To help further simplify the installation process, DSC has placed the PCB on the contact's cover. If you prefer to mount the contact using screws, the new design does not require the removal of the PCB to do so.

Dependable & Versatile

The EV-DW4955 is designed for dependable case- or wall-tamper detection. Depending on how the contact is purposed, it will send a signal to the alarm system if either its casing is opened or if it is forcibly removed from a wall. If the alarm system is armed when this occurs, an alarm will be activated and the central station will be notified of the violation (if programmed to do so).

Value Added

Significantly smaller than many door/window contacts, the EV-DW4955 is housed within a compact casing that allows it to be used for the tightest-fitting installations. Once installed, the contact is inconspicuous and complements the décor of most homes. It is built with reliable 433 MHz technology, uses a long-life lithium battery and is compatible with all current DSC wireless receivers.

Ordering Information:	
EV-DW4955	Wireless Door/Window Contact
	(NA Baud Rate)





Compatibility

The EV-DW4955 is compatible with the following receivers:

PowerSeries[™] Wireless Receivers RF5132-433/PC5132-433 all versions and RF5108-433

MAXSYS® Wireless Receiver PC4164-433

PowerSeries RFK Keypads (RFK5500/RFK5501/RFK5516/RFK5508)

Fixed-Message LCD Keypad with Integrated Wireless Receiver RF5501-433

Envoy™ LCD Self-Contained Wireless Security System NT9005

Specifications

Dimensions	. 1 ^{3/4} " x 1 ^{1/16} " x 11/16"
	(44.5 mm x 27 mm x 17.5 mm)
Battery	. CR2450N (3 V Lithium)
Battery Life	. 5-8 Years (Typical)
Operating Temperature	. 0 to 49 °C (32-120 °F)
Operating Humidity	. 5% to 93% RH