



From Tyco Security Products

## System Enhancement Module DSC PowerSeries™ **Dual Path** (LTE/Ethernet)



### Features That Make a Difference:

- Supports the 4G LTE cellular network
- Fast, Reliable & Secure Wireless Signaling
- No Separate Power Supply Needed
- Remote Monitoring & Control via Web/Mobile
- Expansive Coverage Footprint
- Home Automation & Energy Management
- Easy-to-Read Diagnostics
- Over the Air (OTA) Upgrades
- Easy Remote Programming with AirFX™
- CID and SIA Central Station Signaling

The Alarm.com Dual Path System Enhancement Module (SEM) is the most cost effective and comprehensive solution to migrate compatible DSC PowerSeries PC1616, PC1832 and PC1864 panels to Alarm.com's award-winning interactive services. The Dual Path SEM supports the 4G LTE cellular network and optional Broadband Ethernet. This ensures the longest lifecycle with the most secure and reliable service.

- Enable wireless reporting of alarms and other system events using the LTE wireless (cellular) network and Broadband Ethernet
- Configure and support installations from any browser or smartphone using Alarm.com's familiar and easy-to-use web and mobile support tools, including the Dealer Website and MobileTech
- Enable Alarm.com interactive monitoring and alerting for end users
- Integrate Alarm.com's home automation and energy management services with the SEM's built-in Z-Wave capabilities

### Features

#### Fast, Reliable & Secure Wireless Signaling

The Dual Path SEM sends alarms and system events over both the LTE cellular network and Broadband Ethernet

connection to ensure fast, reliable, and secure communication. A landline phone connection is not required.

#### Remote Monitoring & Control via Web/Mobile

Operation of the SEM from the Alarm.com web and mobile interface is simple and allows system access at any time, from any location. Web features from Alarm.com include viewing system and sensor status/history, arming and disarming the system, setting up and managing user codes, and creating customized e-mail and text message notifications for any type of alarm or non-alarm activity at the property.

#### Easy Remote Programming

Save valuable time and money with Alarm.com's Remote Toolkit. Using the Dealer Website or MobileTech, you can troubleshoot and resolve many customer issues remotely with just the click of a mouse.

#### Functions Include:

- Edit sensor type and name in panel
- Add and delete sensors
- Change entry/exit delays
- Manage user codes
- Upload/Download panel settings

The SEM does not require downloader software or a phone line connection to the control panel.



From Tyco Security Products

## Home Automation & Energy Management

Alarm.com's automation and energy management services allow remote control of Z-Wave devices through web and mobile interfaces. Rules can be created to leverage the entire system of connected devices and security sensors.

## Video Monitoring

Alarm.com's full suite of video services allow customers to keep an eye on their property from anywhere. Customers can view live video feeds and event-triggered recorded clips on their mobile app or customer website. Alarm.com's camera line-up includes HD-quality indoor and outdoor cameras as well as a stream video recorder for 24/7 recording.

## No Separate Power Supply Needed

The SEM does not require its own battery or transformer. It runs on the control panel's AC power and backup battery sources and can function reliably for more than 24 hours during a power outage.

## Easy-to-Read Diagnostics

The SEM's diagnostic LEDs allow installers to monitor the connection between the control panel and the module and between the module and the LTE cellular network. The LEDs also indicate cellular signal strength, which is useful when choosing the best location for the SEM installation.

## Over the Air (OTA) Upgrades

With Over the Air (OTA) firmware upgrades, you can easily keep your SEM inventory current and updated with all the latest features.

## CID and SIA Central Station Signaling

Alarm.com makes it easy to connect to CID and SIA compatible central stations.

## Specifications

Power Requirements .....	12 V nominal, 130 mA (continuous) 2000 mA (instantaneous peaks) maximum (from panel battery)
Cellular Network .....	Dual Band 4G LTE
Panel Interfaces .....	Three keypad bus connections 12V power and ground to panel battery
Alarm.com Module Indicators .....	One module/panel communication status LED, one module power LED, one automation LED, three wireless communication status LEDs
SEM Circuit Board Indicators .....	One LAN LED, one processor LED, one COMM fail LED
Z-Wave Frequency .....	908.4 MHz
Operating Temperature .....	32 to 120°F (0 to 49°C)
Storage Temperature .....	-30 to 140°F (-34 to 60°C)
Humidity .....	90% relative humidity non-condensing
Enclosure Dimensions (L x W x D).....	7.5 x 4.25 x 1.5" (19.05 x 11.43 x 3.81 cm)
Case Material .....	High-impact, ABS plastic

## Carrier

AT&T .....	Part #: ADC-SEM210-PS-AT
Verizon .....	Part #: ADC-SEM210-PS-VZ

## Compatibility

The SEM module is compatible with the following products:

- PowerSeries PC1616, PC1832, PC1864 version 4.2 and newer
- PK5500/5501/5508 and RFK5500/5501/5564 V1.2+
- PTK5507 V1.12+ and WTK5504 1.0+
- IT-100 or PC5320 and SEM module cannot be used on the same system
- SEM Supervision will take the last zone slot of the control panel